

US006344155B1

(12) United States Patent Kitahara et al.

(10) Patent No.: US 6,344,155 B1

(45) **Date of Patent:** Feb. 5, 2002

(54) ELECTRICALLY CONDUCTIVE ADHESIVE COMPOSITION, ELECTRICALLY CONDUCTIVE ADHESIVE SHEET AND USE THEREOF

(75) Inventors: Hiroshi Kitahara; Kensaku Higashi,

both of Shizuoka (JP)

(73) Assignee: Tomoegawa Paper Co., Ltd., Tokyo

(JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 09/541,716

(22) Filed: Apr. 3, 2000

(30) Foreign Application Priority Data

Jan.	28, 2000 (JP)	
(51)	Int. Cl. ⁷	Н01В 1/04
(52)	U.S. Cl	252/502 ; 252/512; 442/6;
		442/117
(58)	Field of Search	252/512, 502;

(JP) 11-098500

442/117, 6

(56) References Cited

U.S. PATENT DOCUMENTS

3,989,531 A	*	11/1976	Orlando et al 524/288
4,742,104 A	*	5/1988	Lindner et al 525/74
5,399,295 A	*	3/1995	Gamble et al 252/511
5,530,044 A	*	6/1996	Mack et al 524/366
5,736,070 A	*	4/1998	Murakami et al 252/512

^{*} cited by examiner

Primary Examiner—Cathy Lam

(74) Attorney, Agent, or Firm—Wenderoth, Lind & Ponack, LLP

(57) ABSTRACT

An electrically conductive adhesive composition which has flexibility and folding endurance and is feasible for use as a shield against electromagnetic waves from a flexible printed circuit, comprises 100 parts by weight of (a) an acrylonitrile-butadiene copolymer, 20 to 500 parts by weight of (b) a phenolic resin and/or an epoxy resin, 1 to 100 parts by weight, per 100 parts by weight of the components (a) and (b) in total, of (c) an electrically conductive filler and 1 to 50 parts by weight, per 100 parts by weight of the components (a) and (b) in total, of (d) a bromine-containing flame retardant.

18 Claims, No Drawings